

US009636944B2

(12) United States Patent Woolley

(10) Patent No.: US 9,636,944 B2

(45) **Date of Patent:** May 2, 2017

(54) IRRIGATION WHEEL TRACTION LUG

(71) Applicant: Joey Woolley, Amarillo, TX (US)

(72) Inventor: Joey Woolley, Amarillo, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 156 days.

(21) Appl. No.: 14/559,915

(22) Filed: Dec. 3, 2014

(65) Prior Publication Data

US 2015/0151570 A1 Jun. 4, 2015

Related U.S. Application Data

- (60) Provisional application No. 61/911,464, filed on Dec. 3, 2013.
- (51) **Int. Cl. B60B 15/02** (2006.01)
- (52) **U.S. CI.** CPC *B60B 15/02* (2013.01); *B60Y 2200/22* (2013.01); *B60Y 2200/224* (2013.01)
- (58) **Field of Classification Search** CPC B60B 15/02; B60Y 2200/224; B60Y 2200/22

USPC 153/209, 225 R, 227, 228; 152/225 R, 152/227, 228

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

| 5,360,045 | A * | 11/1994 | Campbell B60C 27/04 |
|--------------|------|---------|------------------------|
| | | | 152/225 C |
| 5,451,001 | A * | 9/1995 | Kumm A01G 25/09 |
| | | | 239/726 |
| 5,865,916 | A * | 2/1999 | Woolley B60C 27/20 |
| | | | 152/225 R |
| 8,657,215 | B1 * | 2/2014 | Blum B60B 1/10 |
| | | | 239/726 |
| 9,266,506 | | 2/2016 | Korus B60B 15/04 |
| 9,272,571 | | 3/2016 | Niblock B60B 15/22 |
| 2006/0169797 | A1* | 8/2006 | Kaltenheuser B60C 3/04 |
| | | | 239/147 |
| 2009/0084478 | A1* | 4/2009 | Wallet B60C 11/0311 |
| | | | 152/209.13 |
| 2012/0241531 | A1* | 9/2012 | Werner B60C 11/0311 |
| | | | 239/1 |
| | | | |

* cited by examiner

Primary Examiner — S. Joseph Morano
Assistant Examiner — Jean Charleston
(74) Attorney, Agent, or Firm — Shannon L Warren

(57) ABSTRACT

An irrigation wheel traction lug, comprising a lug having a bent-paddle, a base and a one or more chains. Said bent-paddle comprises a first side, a second side and a front portion. Said bent paddle comprises a substantially "V" shape when viewed from above. Said first side and said second side flare backward away from a front portion of said base portion toward a rear edge. and Said lug selectively attaching to an irrigation wheel, having a tread pattern and a rim, by placing said base on said treat pattern, wrapping said one or more chains around said irrigation wheel between said rim and said tread pattern, and securing said lug to said irrigation wheel with said base and said one or more chains.

8 Claims, 15 Drawing Sheets

